



TRUPOSLIP[®] P

slipping agent

Appearance:	beige powder
pH value (1 : 100):	approx. 6

Properties:

TRUPOSLIP P can be used for all aqueous processes in the production of leather.

TRUPOSLIP P reduces the friction in all drum processing, especially when short floats are used by the tannery.

TRUPOSLIP P reduces the mechanical action, degree of knotting, false backs and extent of nubuk grain, particularly for thin pelts and wet-blue.

Application:

The full function of **TRUPOSLIP P** is best produced by dispersing **TRUPOSLIP P** in water prior to application. However, if more convenient, it is also possible to add **TRUPOSLIP P** as a powder and run for 30 mins.

TRUPOSLIP P should be applied in the lime process after the hair has been removed.

The quantity applied depends on the material and the position in the process. The normal quantity offered is 0.1 - 0.3 %, based on the relevant hide weight.

Safety and storage:

It is recommended to wear a protective face mask when weighing.

The product should be kept in a dry place.

08/2004

The information given in this technical leaflet is offered in good faith and is based upon our knowledge and experience of the products used. The suitability of the products mentioned to obtain specific properties or effects are given without obligation or guarantee and should be fully tested by the end user and adapted to suit prevailing works conditions or other products which may be employed.

TRUPOSLIP: registered trademark of TRUMPLER