



# TRUPOTAN<sup>®</sup> AMP

polymer retanning agent

<b>Basis:</b>	synthetic polymers
<b>Appearance:</b>	brown, viscous liquid
<b>Active matter:</b>	approx. 47 %
<b>pH value (1 : 10):</b>	approx. 7
<b>Light fastness:</b>	excellent
<b>Heat yellowing:</b>	excellent

## Properties:

**TRUPOTAN AMP** is a fluid retanning agent based upon synthetic polymers, ideal for producing all types of leather.

**TRUPOTAN AMP** produces leather with very good softness and fullness, with a fine tight grain.

**TRUPOTAN AMP** levels the dyeings without bleaching.

**TRUPOTAN AMP** has excellent light fastness and heat fastness properties.

## Application:

**TRUPOTAN AMP** is normally applied in a fresh float after the neutralisation, but can also be applied during the neutralisation process.

The application pH should lie over pH 4. The quantity applied is normally between 4 and 10 %, based on shaved weight and is dependent on the required filling effect.

**Safety and storage:**

When handling **TRUPOTAN AMP**, normal safety precautions associated with the handling of chemicals should be observed. For more specific details please refer to our safety data sheets.

**TRUPOTAN AMP** can be stored for up to one year, if temperatures below 5 °C and above 40 °C can be avoided. On prolonged storage or extreme temperatures **TRUPOTAN AMP** may exhibit some settlement which can be rectified by either warming and/or stirring the product thoroughly before use.

06/2003

The information given in this technical leaflet is offered in good faith and is based upon our knowledge and experience of the products used. The suitability of the products mentioned to obtain specific properties or effects are given without obligation or guarantee and should be fully tested by the end user and adapted to suit prevailing works conditions or other products which may be employed.

TRUPOTAN: registered trademark of TRUMPLER